Outdoor Enclosure's

Product Summary

E-VISION Out-Door Enclosure's designed for outdoor weather conditions. Enclosures are fabricated out of CRCA steel, CNC programmed, punched, bent, welded and Powder coated with highest quality standards as per the required Outdoor Standards.

Configuration for standard Racks are Welded frame integrated with side walls and down vented top cover, Fan mounting provision on the Front Door for water & dust resistance, rear side of the Enclosure having Pole mounting provision, front glass door with lock and Key provides the security

Outdoor Pole-Mount Enclosures are available in 4U to 12U Variants with 400mm/450mm/500mm depths as per the customer requirements.

Width 550mm.



Features:

- Conforms to IP66 Outdoor Standards
- Adjustable 19" equipment mounting verticals provide the better mounting flexibility maximizing the usable mounting space
- Depth adjustable mounting slots
- Precision engineering capabilities and best efficient software configuration product technology provides the best product quality and fastest delivery in the industry
- Top Panel with ventilation and cable entry from the Bottom

- Cooling fans mounted on Front Door with Top cover for Rain Water & Dust resistance.
- Powder coated finish with pretreatment process meeting all industry standards
- · Pole mounting Provision on the Rear Side
- 100% assured compatibility with all equipment conforming to DIN
 41494. General industrial standard for equipment

Technical Data:

Rack Standard : Conforms to IP66 standard

Construction : Welded

Front Door : Lockable Steel Door

Basic Frame : Steel

Equipment Mounting : DIN Standard Slots

Mounting Angle : 19" Mounting angles made of formed steel

Standard Finish : Powder Coated

Top and Bottom Cover : Welded to Frame, Field Cable entry exit from bottom

Standard Color : Grey Static Load : 20 kgs

Part Code & Dimensions:

	Height OD	Height Usable	Height Usable	Width	Usable	Depth	Usable
Part Code	In mm(H)	in mm (H)	in U (H)	In mm(W)	Width(W)	In mm(D)	In mm(D)
EV-4U-600-GR-IP66	347	267	4U	550	19"	500/600	400

Technical BOM:

S.No.	Part No	Description	
1	EV-4U-600-GR-IP66	IP 66 Outdoor Pole Rack 4U X 550mm W X 600 mm D	
		Construction of Material- 1.2/1.5mm Thick CRCA sheet	
		Each rack includes:	
		A very compact design, welded structure with front accessible	
		The side panels are integrated type & welded with canopy & bottom cover	
		Rigid frame that can be fixed to the pole	
		Front Door with Filter, Louver & T type Lock	
		90CFM, 230V AC Fan - 2 Nos,	
		front door Self-adhesive thermal foam from inside	
		3 Socket PDU 5Amp – 1 No	
		Door Hinges - 2 Nos	
		Cable Glands at bottom side for cable entry	
		19" Angles 4U - 2 Nos for equipment mounting	
		Gasket (As per IP66 Standard)	
		Pole Mounting Brackets at rear side- 2 Nos	
		Hood For Air Inlet at front side	
		Powder Coated Surface	